

+

THREADED & FSW ENDS						FLANGED END												
VALVE SIZE	MAT'L	DIMENSIONS, INCHES				WGT. LBS	VALVE SIZE	ANSI FLANGE	DIMENSIONS, INCHES				WGT lbs.					
		A	B	C ₁	D				A ₁	B	C	D						
1/2"	DI/BRZ	3.62	12.00	2.25	7.00	23	150#	7.25	12.00	2.25	7.00	25	1/2"	7.25	12.00	2.25	7.00	25
	CS/SS	3.65	12.00	2.25	7.00	23	300#	7.50	12.00	2.18	7.00	25		7.25	12.00	2.25	7.00	27
3/4"	DI/BRZ	3.62	12.00	2.25	7.00	23	150#	7.25	12.00	2.25	7.00	27	3/4"	7.62	12.00	2.31	7.00	27
	CS/SS	3.65	12.00	2.25	7.00	23	300#	7.62	12.00	2.25	7.00	27		7.62	12.00	2.31	7.00	27

SPECIFICATION DATA	
CUSTOMER _____	SERIAL No. _____
ORDER No. _____	TAG No. _____
VALVE TYPE _____	QTY. _____
BODY _____	
END CONN. _____	MAX. Δ P _____
INLET PRESS. _____	SET AT _____
TEMP. RANGE _____	VALVE ACTION: RISE IN TEMPERATURE TO <input type="checkbox"/> OPEN <input type="checkbox"/> CLOSE
	VALVE SEAT _____ Cv _____
	CAPILLARY LENGTH _____ BULB _____
MISC. _____	CERTIFIED _____ DATE _____

RICHARDS INDUSTRIES
CINCINNATI, OHIO
U.S.A.

VALVE GROUP ○

DRAWN BY: JLA CHECKED BY: _____ DATE: 5/7/96 DATE: _____	MK85
---	------

FN: MK85 1/2-3/4" MARK 85 FAIL SAFE TEMPERATURE REGULATOR	
---	--

+