


+

THREADED & FSW ENDS						FLANGED END								
VALVE SIZE	DIMENSIONS, INCHES					WGT. lbs.	VALVE SIZE	ANSI FLANGE	DIMENSIONS, INCHES					Wt. lbs.
	A	B	C	D	E				A ₁	B	C	D	E	
1/2	5.31	10.74	3.43	7.12	10.00	48	150#	11.50	10.74	3.43	7.12	10.00	50	
3/4	5.31	10.74	3.43	7.12	10.00	53	300#	11.50	10.74	3.43	7.12	10.00	52	
1	5.68	11.06	3.56	7.12	10.00	58	150#	11.50	10.74	3.43	7.12	10.00	57	
1 1/4	6.00	11.43	3.75	7.12	10.00	58	300#	11.50	10.74	3.43	7.12	10.00	59	
1 1/2	8.00	15.31	5.00	10.62	10.00	90	150#	11.50	11.06	3.56	7.12	10.00	62	
2	8.00	15.31	5.00	10.62	10.00	92	300#	11.50	11.06	3.56	7.12	10.00	64	
							150#	11.50	11.43	3.75	7.12	10.00	62	
							300#	11.50	11.43	3.75	7.12	10.00	66	
							150#	14.50	15.31	5.00	10.62	10.00	96	
							300#	14.50	15.31	5.00	10.62	10.00	102	
							150#	14.50	15.31	5.00	10.62	10.00	102	
							300#	14.50	15.31	5.00	10.62	10.00	106	

SPECIFICATION DATA	
CUSTOMER _____	SERIAL No. _____
ORDER No. _____	TAG No. _____
VALVE TYPE _____	QTY. _____
BODY _____	
END CONN. _____	MAX. ΔP _____
INLET PRESS. _____	SET AT _____
TEMP. RANGE _____	VALVE ACTION: RISE IN TEMPERATURE TO <input type="checkbox"/> OPEN
	<input type="checkbox"/> CLOSE
	VALVE SEAT _____ Cv _____
	CAPILLARY LENGTH _____ BULB _____
	MISC. _____
	CERTIFIED _____ DATE _____



RICHARDS INDUSTRIES
CINCINNATI, OHIO
U.S.A.

VALVE GROUP °

FN: MK87	DATE	5/31/96
	CHECKED BY	

1/2"-2" MARK 87

EXTERNAL PILOT OPERATED TEMPERATURE REGULATOR

+